

MINI INCUBATOR

INCUBATORS

MAIN FEATURES:

- > Small Bench Top Incubator
- > Door with large window
- > Precise temperature control by hydraulic thermostat
- > Ideal for microbiology or hematology applications
- > Corrosion resistant chamber
- > Three shelf levels

TECHNICAL SPECIFICATONS

TECHNICAL SPECIFICATONS	
Model	Mini Incubator
Voltage	230 V / 50-60 Hz 115 V / 50-60 Hz
Power	70VA
Temperature range	Ambient + 5°C to 60°C
Controls	Analog
Stability	±0,6°C at 37°C
Accuracy	±5°C
Capacity	10 liters
Ambient operation range	4°C to 65°C
Net weight	3,8kg
Dimensions	285 x 280 x 335mm



Analog 10I incubator is compact and economically priced, yet offers features not typically found in a basic incubator. The housing is all metal, as is the door frame. See-through acrylic door lets you view contents without opening the door. One shelf is included, and can be adjusted to two different levels - additional shelves can be purchased to increase storage capacity.

The heating elements in incubator are incorporated into the bottom and sides of the aluminum chamber. This provides better temperature stability and uniformity than other incubators in it's class.

A grommet hole in the top of the unit can hold a thermometer for accurate temperature setting.

ORDERING INFORMATION

MINI INCUBATOR	
230V / 50-60Hz	780.400
MINI INCUBATOR	
115V / 50-60Hz	1780.400

We reserve the right to alter specification details etc. without prior notice or liability! V:11-19

DOMEL

DOMEL, d.o.o., Otoki 21, 4228 Železniki
BU Laboratory Systems, Na Plavžu 79, 4228 Železniki

Phone: +386 4 5117 525
E-mail: info.labs@domel.com
WEB: <http://labs.domel.com>

